

| REVISIONS | | | |
|-----------|-------------------------|----------|----------|
| REV | DESCRIPTION | DATE | APPROVED |
| 1 | PROTOTYPE RELEASE | | |
| A | RELEASED PER EDR 42-531 | 12-21-94 | AKS |
| B | REVISED PER ECO 3058 | 2-16-95 | AKS |


SHT 1 COVER SHEET
 SHT 2 LINE FILTER
 SHT 3 TRANSFORMER, DC RECTIFIED
 SHT 4 DC REGULATED

7. FOR 100V/115V UNITS INSTALL JUMPERS R1, R2
REMOVE JUMPER R3
FOR 230V/240V UNITS INSTALL JUMPER R3
REMOVE JUMPERS R1, R2
6. LUG1, LUG3 AND LUG4 ARE 0.250 QUICK DISCONNECT LUGS.
5. LUG2 IS A 0.187 QUICK DISCONNECT LUG.
4. ALL FUSES ARE 250V, 5 X 20MM.
FOR IEC ASSY: F1 = T1.0A
F2, F3 = F2.0A
F4, F5 = F1.6A
FOR UL ASSY: F1 = 1.0A. SLOW BLOW
F2, F3 = F2.0A
F4, F5 = F1.6A
3. ALL 0.1UF BYPASS CAPACITORS ARE 50V +80/-20% Z5U.
2. ALL CAPACITOR VALUES ARE IN MICROFARADS, 16V MINIMUM.
1. ALL RESISTOR VALUES ARE IN OHMS, 1/10W 5%.

NOTES - UNLESS SPECIFIED OTHERWISE:

COVER SHEET

| | | | | | |
|-----------|----------|----------|---------------|------------|--------|
| APPROVALS | | DATE | PCB SCHEMATIC | | |
| OWN BY: | AKS | 08-20-94 | POWER SUPPLY | | |
| CHKD BY: | | | DP-4+ | | |
| APPD BY: | | | SIZE | DWG. NO. | REV |
| | | | B | 4010025201 | B |
| USED ON: | DP-4 PRO | SCALE | — | SHEET | 1 DF 4 |



PRIMARY

LINE FILTER

ENSONIQ Corp

PCB SCHEMATIC

POWER SUPPLY

DP-4+

| SIZE | DWG. NO. | REV | SHEET | OF |
|------|------------|-----|-------|----|
| B | 4010025201 | B | 2 | 4 |

